AGRISTAR STOU 15W-40

Last Updated: 09.01.2025 Product Code: AT0036



AGRISTAR STOU 15W-40 is a premium-quality STOU that offers superior performance in engines, transmissions, hydraulic, and wet brake applications for a wide range of agricultural equipment and farming applications where this grade of oil is required.

APPLICATION

Use as received in engines, transmissions, hydraulic systems, power take-off systems, power steering units, hydrostatic transmissions, and gear drive units when one multi-functional lubricant is recommended or required.

BENEFITS

- One oil for several applications, so reducing the number of grades needed in stock.
- Wide-ranging specification assures compliance with many manufacturer requirements.
- Reduces the risk of filling the wrong lubricant when several applications are due for changing.
- Strong STOU engine performance characteristics meet a large range of manufacturers specifications.
- Excellent cold weather performance.
- Versatile transmission performance, suitable for manual, powershifts, CVT's and hydrostatic drives.
- Suitable for wet brake applications.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

- API CG-4/SF, API GL-4
- ACEA E3
- Massey Ferguson M1139, M1144, M1145
- John Deere J20C, J27A
- FORD M2C-86B/C, M2C-134D, M2C-159B/C
- CASE Int. MS-1204/6/7/9
- CASE New Holland MAT 3535
- Caterpillar T0-2
- Allison C-4
- FORD New Holland 82009201/2/3
- ZF TE-ML 06A, 06B, 06C, 06D, 07B
- Mercedes-Benz 227.1
- Sperry Vickers/Eaton M2950S, I-280-S

TYPICAL PROPERTIES

Specific Gravity @ 15.6°C	0.894
Kinematic Viscosity @ 100°C (cSt)	16.1 typical

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health, and disposal information, which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.