SIAIR Lubricants

AGRISTAR UTTO is a high performance Universal Tractor Transmission Oil designed to provide exceptional protection to agricultural and off highway equipment especially those operating under severe load conditions.

APPLICATION

Use as received where a common lubricant for transmissions, differentials, final drives, hydraulic and wet brake applications is required.

BENEFITS

- Excellent extreme pressure (EP) performance maximizes component life.
- Formulated to provide exceptional anti-wear and anti-corrosion capabilities.
- Strong yellow metal protection and multi-metal capability minimises stock inventories.
- Excellent thermal stability promotes greater oxidation control for longer fluid life.
- Suitable for wet brakes and PTO applications.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API GL-4
- John Deere JHD J20C, J20D, J21A
- Ford M2C-86B/C, M2C-134D
- CASE MS-1204, 1206, 1207, 1209
- CASE New Holland MAT 3525, 3526
- New Holland NWH 410B
- Kubota UDT
- Sperry/Vickers Eaton I-286-S, M-2950-S
- Caterpillar TO-2
- Allison C-4
- Massey Ferguson M1135, M1141 (Permatran III), M1143, M1145
- Volvo WB101 (97303)
- JCMAS HK P-041 & P-042
- ZF TE-ML 03E, 05F, 06K, 17E, 21F

TYPICAL PROPERTIES

Specific Gravity @ 15.6°C	0.883
Kinematic Viscosity @ 100°C (cSt)	10.1 typical

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.