

AGRISTAR UTTO HY-SYNTH is a very high performance Universal Tractor Transmission Oil formulated using the latest synthetic technology. Designed to provide exceptional protection to agricultural and off highway equipment especially those operating under severe load conditions.

## **APPLICATION**

Use as received where a common lubricant for transmissions, differentials, final drives, hydraulic and wet brake applications is required.

## **BENEFITS**

- Enhanced extreme pressure (EP) performance maximizes component life.
- Formulated to provide exceptional anti-wear and anti-corrosion capabilities.
- Strong yellow metal protection and multi-metal capability minimises stock inventories.
- Outstanding thermal stability promotes greater oxidation control for longer fluid life.
- Suitable for wet brakes and PTO applications.
- Meets the latest specifications required for modern agricultural machinery.

## **PERFORMANCE PROFILE**

Suitable for use where the following specifications are required;

- API GL-4
- AGCO-Allis
- Allis-Chalmers PF-821XL
- CASE MS-1204, 1206, 1207, 1209
- CASE New Holland MAT 3509, 3525, 3526
- CLAAS / Renault Agriculture requirement
- New Holland NH 405B, NH410B
- John Deere J20C, J20D
- Ford M2C-134D, FNHA 2C 201.00/200.00
- Komatsu AXO 80
- Kubota UDT, Super UDT
- Massey Ferguson M1143, M1145
- McCormick HTX
- VALTRA G2-08
- Volvo WB102 (97304)
- ZF TE-ML 03E, 03L, 05F, 17E, 21F

## **TYPICAL PROPERTIES**

Specific Gravity @ 15°C	0.861
Kinematic Viscosity @ 100°C (cSt)	7.6 (typical)
Pour Point	40

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our

# AGRISTAR UTTO HY-SYNTH

Last Updated: 09.01.2025  
Product Code: AT0420



product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.