

# AIRLINE LUBRICANT EP22

Last Updated: 09.01.2025  
Product Code: AIR0022



AIRLINE LUBRICANT EP22 is a high-quality low viscosity oil designed for the lubrication of all types of pneumatic tool which require this grade of product.

## **APPLICATION**

Recommended for all types of air tool such as torque wrenches, drills, jackhammers, saws etc. Also suitable for air rams and motors, as well as for general purpose industrial applications.

## **BENEFITS**

- Exceptional EP and anti-wear capabilities to provide protection even in the most demanding conditions.
- Formulated for maximum rust and corrosion resistance for extended component life.
- Low viscosity ensures rapid circulation to get to work faster.
- Excellent anti-foam properties ensures quick release of air from the oil.

## **TYPICAL PROPERTIES**

|                             |                                   |
|-----------------------------|-----------------------------------|
| Colour & Appearance         | Pale straw coloured, clear liquid |
| Density @ 20°C              | 0.856 kg/m <sup>3</sup>           |
| Kinematic Viscosity @ 40°C  | 22 cSt                            |
| Kinematic Viscosity @ 100°C | 4.2 cSt                           |

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.