AUTOTRANS MULTIVEHICLE CVT FLUID

Last Updated: 09.01.2025 Product Code: AD0073



AUTOTRANS MULTIVEHICLE CVT FLUID is a premium, high performance, fully synthetic fluid designed to meet the exacting specifications of Continuously Variable Transmissions found in many modern vehicles.

APPLICATION

Formulated to meet the wide range of CVT requirements from manufacturers such as HONDA, MAZDA, MITSUBISHI, NISSAN, TOYOTA, KIA and HYUNDAI, as well as many European OEM's using CVT transmissions, such as VW/AUDI and BMW/MINI.

BENEFITS

- Outstanding anti-wear protection to extend transmission life.
- Exceptional anti-shudder capabilities to promote smooth power transmission.
- Offers enhanced shift quality even in extreme low temperature environments.
- Exceptional fluidity throughout the high-low temperature range.
- Formulated to maintain viscosity and film strength even during high temperature operation.
- Excellent oxidation and thermal resistance for longer component and fluid life.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- BMW/MINI EZL799, EZL799A
- MINI COOPER ZF CVT V1
- CHRYSLER/JEEP NS-2, CVT+4
- FORD M2C 928-A (CFT 23)
- FORD M2C 933-A (CFT 30)
- FIAT CVT N.G.
- GM DEX CVT, CVTF I-Green2
- HONDA HMMF (without starting clutch)
- HONDA HCF-2, e:HEV, iMMD
- HONDA Ultra HEVF-Type 1
- HYUNDAI/KIA CVT-1
- JATCO CVT 8 Hybrid
- MAZDA JWS 3320
- MERCEDES-BENZ MB 236.20
- MITSUBISHI CVTF-J1, J4
- MITSUBISHI CVTF-J4+, ECO J4
- MITSUBISHI SPIII (CVT only)
- NISSAN NS-1, NS-2 / 2V, NS-3
- PEUGEOT PSA 9735EF
- RENAULT Elf Matic CVT
- RENAULT CVT CK/SK/FK
- SUBARU iCVT, iCVT-FG, ECVT
- SUBARU Lineartronic CVT / II
- SUBARU Lineartronic CVT 3
- SUBARU Lineartronic HT CVT
- SUZUKI CVTF TC
- SUZUKI NS-2
- SUZUKI CVT Green 1, 2
- SUZUKI CVT Green 1V

AUTOTRANS MULTIVEHICLE CVT FLUID

Last Updated: 09.01.2025 Product Code: AD0073



- SUZUKI CVTF TC, 3320, 4401
- TOYOTA/LEXUS CVTF TC, FE
- TOYOTA THS II / Prius
- TOYOTA THS 5th Gen
- VAUXHALL/OPEL 7-sp CVT
- VAUXHALL/OPEL 95529854
- VOLVO CVT 4959
- VW/AUDI TL 521 16
- VW/AUDI G 052 516
- VW/AUDI TL 521 80
- VW/AUDI G 052 180 A2
- VW/AUDI Multitronic
- Not recommended for DCT transmissions

TYPICAL PROPERTIES

Appearance	Yellow/amber
Specific Gravity @ 15.6°C	0.850
Kinematic Viscosity @ 100°C (cSt)	7.3 (typical)
Flash Point (closed cup) °C	186

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.