

AUTOTRANS MV is a premium, multi-vehicle, fully synthetic fluid primarily designed to meet the exacting requirements of the latest automatic transmissions of Asian/Far Eastern origin found in many Japanese and Korean vehicles.

## **APPLICATION**

Especially formulated to meet the latest requirements of manufacturers such as HONDA, MAZDA, MITSUBISHI, NISSAN, TOYOTA, KIA and HYUNDAI, as well as many European OEM's using JATCO and Aisin Warner transmissions of the same origin, such as JAGUAR, LAND ROVER and VW/AUDI, and suitable for use where GM Dexron VI fluid is specified.

## **BENEFITS**

- Outstanding anti-wear protection to extend transmission life.
- Offers smooth shift quality even in extreme low temperature environments.
- Extended oil durability offers longer change interval capability.
- Exceptional fluidity throughout the high-low temperature range.
- Formulated to maintain viscosity and film strength even during high temperature operation.
- Compatible with all types of seal materials.
- Excellent oxidation and thermal resistance for longer component and fluid life.

## **PERFORMANCE PROFILE**

Suitable for use where the following specifications are required;

- GM Dexron VI
- FORD Mercon-LV
- FORD M2C 922-A1 for Durashift 5F31J
- JASO M315 Class 1A
- AISIN WARNER AW-1, F21
- ATF JWS 3309, 3324, N402
- JATCO K17, 3100 PL085
- BMW 83 22 0 397 114
- BMW 83 22 2 163 514
- Chrysler/Jeep MS 9602
- Chrysler/Jeep ATF +4
- HONDA DW-1, Z1
- HYUNDAI/KIA SP-IV, SPH-IV
- HYUNDAI/KIA Red-1K
- HYUNDAI/KIA 040000C90SG
- HYUNDAI/KIA JWS 3309 T-4
- HYUNDAI/KIA NWS-9638 T-5
- JAGUAR ATF 3100 PL085,
- JAGUAR ATF K17
- LAND ROVER LRN402
- LAND ROVER AWS3309
- LAND ROVER LR002748
- MAZDA FZ
- MITSUBISHI ATF-J3
- NISSAN Matic S, N402
- SAAB 93 165 147
- SUBARU ATF-HP

- SUZUKI ATF 3314, 3317
- TOYOTA/LEXUS WS
- TOYOTA/LEXUS JWS 3324
- VOLVO 97342 (AT102)
- VOLVO 1161540, 1161640
- VW/AUDI G 055 540
- VW/AUDI G 055 025
- VW/AUDI G 052 533
- VW/AUDI G 052 990
- Not recommended for CVT or DCT transmissions

## **TYPICAL PROPERTIES**

Appearance	Red
Specific Gravity @ 15.6°C	0.850
Kinematic Viscosity @ 100°C (cSt)	6.3 (typical)

## **HEALTH & SAFETY**

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.