

CLASSIC GEAR OIL SAE 140 GL-1

Last Updated: 09.01.2025
Product Code: AG0140



CLASSIC GEAR OIL SAE 140 GL-1 is a mineral oil based, monograde non-EP grade suitable for use where the manufacturer specifies this type of oil.

APPLICATION

Designed for use in equipment where a gear lubricant formulated without extreme pressure (EP) additives is specified. Formulated to protect period seal and gasket materials and to be completely compatible with phosphor-bronze bearings as well as other yellow metal components. Primarily for use in pre-1950 car, commercial and agricultural gearboxes and transmissions where an API GL-1 gear oil is required.

Note: this non-EP formulation may not be suitable for use in many automotive applications built after 1951 - use in more modern equipment may cause unsatisfactory performance or possible harm or damage - please check compatibility before use.

BENEFITS

- Excellent lubricity for added component protection.
- Incorporates good natural film strength and excellent corrosion resistance to protect component parts.
- Compatible with yellow metal components.
- Designed to prolong fluid life and minimize oil consumption.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

API GL-1

TYPICAL PROPERTIES

Specific Gravity @ 15.6°C	0.903
Kinematic Viscosity @ 100°C (cSt)	28.7
Flash Point COC (°C)	>250
Pour Point (°C)	-10

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.