

COMPRESSOR OIL 150

Last Updated: 09.01.2025
Product Code: CL0465



COMPRESSOR OILS 150 is a high performance, ashless oil designed for the lubrication of reciprocating and rotary compressors, and meet the requirements of most vane compressors for 2000 hour services.

APPLICATION

Use as received for the lubrication of reciprocating and rotary compressors, as well as vacuum pump equipment which requires this specification of lubricant.

BENEFITS

- Effective control of carbon deposits and sludge formation.
- Carefully selected refined mineral oils ensure resistance to oxidation.
- Resists emulsification.
- Helps prevent filters from blocking.
- Minimises equipment downtime.
- Suitable for use in equipment with air discharge temperatures up to 2200C.

PERFORMANCE PROFILE

- DIN 51506 VDL (Piston Air Compressor Oils)

TYPICAL PROPERTIES

SAE Viscosity No.	40
Viscosity @ 40°C	143
Viscosity @ 100°C	14.2
Density	0.885

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.