SIAIR Lubricants

FLEETLUBE 10W-30 is a multigrade engine oil suitable for use in both petrol and diesel engines.

APPLICATION

Recommended for use in vehicles where a 10W-30 grade engine oil meeting the specifications below is required by the engine manufacturer. The cost-effective formulation is designed primarily for use in older generation vehicles where the very latest specifications of engine lubricant are not a requirement.

Please note - not suitable for engines meeting EURO 4 or later emissions standards.

BENEFITS

- High shear stability.
- Promotes easy starting in cold conditions.
- Suitable for both turbocharged and normally aspirated petrol and diesel engines.
- Enhanced anti-wear performance for reduced engine wear.
- Excellent sludge control for stop-go city motoring.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API CG-4/SJ
- ACEA E2
- MAN 271
- Mercedes-Benz 228.1

TYPICAL PROPERTIES

Specific Gravity @ 15.6°C	0.877
Kinematic Viscosity @ 100°C(cSt)	10.9 typical

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.