

# FLEETLUBE 15W-40

Last Updated: 09.01.2025  
Product Code: AE0008M



FLEETLUBE 15W-40 engine oil is designed to meet the requirements of both turbocharged and naturally aspirated diesel and petrol engines. Manufactured from high quality mineral base oils incorporating high performance viscosity index improvers, anti-oxidant, anti-wear and detergent dispersant additives for extended engine life.

## **APPLICATION**

For use in light and heavy duty commercial vehicles, vans, off highway plant and passenger cars where this specification of oil is required by the manufacturer.

Please note - not suitable for engines meeting EURO 4 or later emissions standards.

## **BENEFITS**

- High shear stability.
- Excellent sludge control for stop start motoring.
- Anti-wear performance for reduce engine wear.
- Bore polish protection.

## **PERFORMANCE PROFILE**

Suitable for use where the following specifications are required;

- API CG-4/SJ
- ACEA E3
- Mercedes-Benz 228.3
- VOLVO VDS
- MACK EO-M
- MAN 271

## **TYPICAL PROPERTIES**

Specific Gravity @ 15.6°C	0.881
Kinematic Viscosity @ 100°C (cSt)	14.2
Kinematic Viscosity @ 40°C (cSt)	108.9
VI	141
Flash Point COC (°C)	220
Pour Point (°C)	-32
TBN mg KOH/g	9.18

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.