

# FLEETLUBE HD 15W-40

Last Updated: 09.01.2025  
Product Code: AE0012



FLEETLUBE HD 15W-40 engine oil is designed to meet the requirements of turbocharged / naturally aspirated diesel and petrol engines.

## **APPLICATION**

For use in light and heavy duty commercial vehicles, vans, off highway plant and passenger cars where this specification of oil is required by the manufacturer.

## **BENEFITS**

- High shear stability.
- Excellent sludge control for stop start motoring.
- Anti-wear performance for reduce engine wear.
- Bore polish protection.

## **PERFORMANCE PROFILE**

Suitable for use where the following specifications are required;

- API CF-4/SG

## **TYPICAL PROPERTIES**

Specific Gravity @ 15.6°C	0.882
Kinematic Viscosity @ 100°C (cSt)	15.5
Kinematic Viscosity @ 40°C (cSt)	108.0
VI	152
Flash Point COC (°C)	217
Pour Point (°C)	-30

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.