

FLEETLUBE SAE 10

Last Updated: 09.01.2025
Product Code: AE0017

SAR Lubricants

FLEETLUBE 10 is a monograde engine oil designed to meet the requirements of many naturally aspirated diesel and petrol engines.

APPLICATION

Primarily for use in commercial vehicles, vans, plant, off-highway equipment and passenger cars where this specification of oil is required by the manufacturer. Fleetlube SAE 30 is also commonly used in many types of smaller agricultural machinery, such as 4 stroke petrol-engined lawnmowers.

BENEFITS

An API SG/CF specification diesel/petrol engine oil which can also be used in many transmission and hydraulic applications for plant, off-highway and agricultural equipment which require SAE 10, SAE 20, SAE 30, SAE 40 & SAE 50 viscosities.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API SG/CF

TYPICAL PROPERTIES

Kinematic Viscosity @ 100°C (cSt)	4.9
Density @ 15.6°C	0.869

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.