

HYPOID GEAR OIL 85W-140 LS GL-5

Last Updated: 09.01.2025
Product Code: AG0451



HYPOID GEAR OIL 85W-140 LS GL-5 is a high performance, heavy-duty rear axle lubricant which incorporates a special friction modifier additive system in high-quality, solvent refined base stocks to obtain optimum slip function in Limited Slip differentials subject to severe or extreme operating conditions.

APPLICATION

It is primarily recommended for rear axles incorporating Limited Slip capability, and is suitable for use in both high-performance road car and heavy-duty commercial vehicle applications where this specification of lubricant is recommended.

BENEFITS

- Incorporates special friction-modifier system to optimize Limited Slip function.
- Exceptional wear protection even under the most severe operating conditions.
- Incorporates an enhanced package of rust and corrosion inhibitors for longer component life.
- Dramatically reduces axle noise in Limited Slip differentials.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API GL-5
- MIL-L-2105D

TYPICAL PROPERTIES

Density @ 20°C	0.880
Kinematic Viscosity @ 40°C (mm ² /s)	378.0
Kinematic Viscosity @ 100°C (mm ² /s)	27.8
Viscosity Index (Method: D 2270)	101
Flash Point (°C)	237
Pour Point (°C)	- 25

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.