

MEDIUM CHAIN OIL

Last Updated: 09.01.2025
Product Code: IB0030

SAR Lubricants

MEDIUM CHAIN OIL is formulated using highly refined mineral base stocks and a specially selected additive package designed to reduce 'fling' and offer excellent all round performance for many general purpose industrial applications including the lumber industry, forestry, woodyard and estate management requirements. Provides excellent corrosion protection and improved chain performance in a wide range of climatic conditions.

APPLICATION

Designed for the lubrication of all types of drive and conveyor chains, bearings and linkages in a wide range of applications. Select the appropriate grade and apply per the equipment manufacturers instructions.

BENEFITS

- Formulated to include anti-wear capabilities for prolonged chain life.
- Special 'tackifier' reduces 'fling' and ensures that the film of oil is not ejected from the chain.
- Excellent penetration into pins and links.
- Enhanced anti-corrosion protection capabilities.
- Offers wide operating temperature ranges between -150°C and +120°C.

TYPICAL PROPERTIES

Viscosity @ 40°C	100
Colour	Amber
Density	0.887

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.