

MOULD OIL 32

Last Updated: 09.01.2025
Product Code: CM0931

MOULD OIL 32 is high quality blend of solvent refined mineral oil and specialist release agent additives designed for use as a mould release agents and also for pre-treatment and cleaning of concrete/cement mixing equipment.

APPLICATION

MOULD OIL 32 & 46 are designed to promote excellent mould release, and are also ideal for the pre-treatment and cleaning of all types of concrete/cement mixing equipment. Both are suitable for application by roller or brush, and compatible with most mould materials.

Please check compatibility before application and use in accordance with equipment manufacturers recommendations.

BENEFITS

- Suitable for use on most surfaces including metals, sealed wood, fiberglass, plastics etc.
- Provides good surface finish together with excellent mould release properties.
- Exceptional performance characteristics prevent bonding and facilitate easier clean up when used in mixing equipment.
- Easy application by roller or brush.

TYPICAL PROPERTIES

Appearance	Amber Fluid
Viscosity @ 40°C	32 cSt
Specific Gravity 15.6°C	0.850
Flash Point (COC) °C	> 220

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.