

MULTILUBE OIL 680

Last Updated: 09.01.2025
Product Code: ML0680



MULTILUBE OIL 680 is a premium quality, ashless lubricant formulated to meet the requirements of slideway, hydraulic systems, industrial gearboxes and general lubrication applications, and where one oil is required as a multifunctional lubricant.

APPLICATION

Use as received where applications require a zinc-free, multifunctional lubricant in an ISO 32, ISO 46, ISO 68, ISO 100, ISO 150, ISO 220, ISO 460 and ISO 680 viscosity, to the specifications listed below.

BENEFITS

- Multifunctional performance to help reduce lubricant inventories.
- Excellent anti-wear performance.
- Prevents any stick / slip on slideways.
- Elevated corrosion resistance protects machine tools from rust.
- Outstanding cutting fluid compatibility with excellent demulsifying capabilities.

TYPICAL PROPERTIES

Viscosity @ 40°C	612 - 748
Specific Gravity @ 15.6°C	0.910

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.