

MULTIVEHICLE MTF 75W80 GL-4+

Last Updated: 09.01.2025
Product Code: AG0640



MULTIVEHICLE MTF 75W80 GL-4+ is a fuel-efficient, manual transmission fluid formulated with the very latest additive technology to offer high levels of gear protection and synchronizer compatibility. Designed to be especially suitable for a wide range of modern passenger car transmission requirements where gearbox and differential share the same unit.

APPLICATION

Formulated for applications where an API GL-4 or GL-4+ gear oil of this viscosity is specified. Particularly recommended for use in many modern passenger car manual transmissions from a wide range of manufacturers as listed below.

BENEFITS

- Proven synchronizer protection far in excess of standard API GL-4 specification fluids.
- Fuel-efficient formulation with exceptional low temperature performance.
- Formulated to offer high load-carrying capability for superior bearing and gear protection.
- Excellent cleanliness, with enhanced anti-corrosion and anti-oxidation performance.
- Wide range of applications gives true multi-vehicle capability to help reduce stocks/inventories.

PERFORMANCE PROFILE

Suitable for use where the following are specified by the manufacturer;

- BMW MTF LT-2
- GM 1940004, 1959104
- GM 1940764, 1940768
- GM 1940182
- GM W16612 (dry DCT)
- FIAT MZ1, MZ6
- FORD M2C 186-A
- FORD M2C 200-C
- FORD M2C 200-D2 (dry DCT)
- Honda Special MTF, MTF-II
- Honda MTF-III
- Nissan MT-X
- Nissan MT-XZ TL (JR Type)
- PSA B71 2330 (EZL 848)
- PSA B71 2315
- PSA B71 2316 (HBVFE)
- Renault DC4 DWS (dry DCT)
- Volvo 97308, 97309
- VW G 052 512 (dry DCT)
- VW G 055 512 (dry DCT)
- VW G 052 171, G 052 178
- VW G 052 726, G 060 726
- VW G 50, G 009 317
- VW G 052 527 A2
- VW G 070 726 A2

Also suitable for most passenger car manual transmissions as specified by the manufacturers listed below;

- Alfa Romeo/FIAT
- Chrysler/Jeep/Dodge

MULTIVEHICLE MTF 75W80 GL-4+

Last Updated: 09.01.2025
Product Code: AG0640



- Hyundai/KIA
- Jaguar Land Rover
- Mazda
- Mercedes-Benz/SMART
- Mitsubishi
- Renault/Dacia
- Suzuki
- Toyota

TYPICAL PROPERTIES

Density @ 15.6°C	0.855
Viscosity@ 100°C	8.9 cSt
Viscosity @ 40°C	50.9 cSt
Viscosity Index	156

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.