

SARCOOL TEC 5819

Last Updated: 09.01.2025
Product Code: IC05819



SARCOOL TEC 5819 is a boron free, semi-synthetic metalworking fluid. The product is ideal for use in machining and grinding cast iron as well as a wide range of mixed metals including stainless steels, aluminium alloys and titanium. Provides enhanced cooling as well as medium to high lubricity due to its well-balanced formulation.

APPLICATION

Applications — wide range of machining and grinding operations

Metals — cast iron as well as a wide range of mixed metals including aluminium alloys, stainless steels and titanium alloys

Notes — running at or above 7% offers the best sump life and corrosion inhibition on cast iron chips

— in mixed-metal situations, concentration control, over 7%, is critical to fight galvanic corrosion

BENEFITS

- Boron and formaldehyde-releaser free.
- Low foaming in modern high pressure, high-volume applications.
- Excellent compatibility and lubrication for machining sensitive high silica aluminium alloys.
- Proven performer in titanium milling applications.
- Performs well where traditional soluble oils may not cool sufficiently.
- Provides superior corrosion inhibition on all ferrous metals.
- Uses standard metalworking recycling and disposal techniques.

PERFORMANCE PROFILE

Recommended Metalworking Concentrations

Grinding	3.0% – 5.0%
Light Duty	5.0% – 6.0%
Medium Duty	7.0% – 8.0%
Heavt Duty	8.0% – 10.0%
Design Concentration Range	3.0% – 10.0%

TYPICAL PROPERTIES

Appearance (Concentrate)	Amber liquid
Appearance (Emulsion)	Semi translucent
pH (5% emulsion)	8.8 – 9.1
IP 287 Breakpoint	2.5%
Mineral Oil Content	Low
Refractometer Conversion Factor	2.0
Make Up Water Hardness	0 – 450 ppm

FLUID MAINTENANCE

To check and maintain fluid concentration a refractometer is recommended, the resulting reading multiplied by the refractometer

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)

Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk

Registered in England: 05866783 VAT Registration No: 889171963

conversion factor will give the actual concentration strength. Maintaining a consistent concentration is paramount to prolonging the fluid sump life. To promote long service life, it is strongly advised that coolant systems are thoroughly sterilised with a System Cleaner prior to coolant changes (see Sarsol System Cleaner Technical Data Sheet for further information and guidelines).

Further tests for bacteria, fungus, pH and tramp oil contamination are available through our Cooltrak Fluid Management Service. This service offers guidance and assistance for users to comply with current HSE legislative requirements. Please contact us for further details.

HEALTH & SAFETY, STORAGE AND DISPOSAL

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.