

# SARCUT L 8

Last Updated: 09.01.2025  
Product Code: MW0008



SARCUT L 8 is a low viscosity high performance neat cutting oil, a chlorine free formulation with inactive sulphur, advanced lubricity additives and an anti-mist agent to improve operator and machine shop conditions.

## **APPLICATION**

Use as received for applications requiring a low viscosity oil. Formulated with lubricity esters to give outstanding performance on operations requiring no sulphur or chlorine in the formulation, for ferrous and use on yellow metals.

Can be used for all forms of cutting, grinding and lapping operations and is suitable for use as a lubricating oil where a viscosity grade of ISO 10 is acceptable.

## **BENEFITS**

- Low viscosity ensures good flushing of machine debris.
- Suitable for a variety of machining operations ferrous, yellow metals and sensitive aluminium alloys.
- Suitable for light to medium severity tapping, general machining and drilling operations.

## **TYPICAL PROPERTIES**

|                           |                |
|---------------------------|----------------|
| Appearance                | Pale Amber Oil |
| Specific Gravity @ 15.60C | 0.836          |

Kinematic Viscosity @ 40C: 6.0 – 8.0 cSt

Chlorine: No

Sulphur: Yes

Ester: Yes

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.