

SARCUT SLA 32

Last Updated: 09.01.2025
Product Code: MW0318



SARCUT SLA 32 is a medium viscosity high performance dual purpose neat cutting oil suitable for machining operations such as tapping, threading, turning, gear hobbing on medium tensile steels and non-ferrous metals. Its high performance chlorine free EP additive package makes it an ideal product for rationalising several applications under one product.

APPLICATION

Use as received for applications requiring a medium viscosity oil with chlorine free EP additives and esters with excellent lubricity to give outstanding performance on operations requiring no active sulphur in the formulation, i.e. for use on yellow metals.

BENEFITS

- High performance EP and lubricity characteristics..
- Suitable for a variety of machining operations on yellow metals.
- Suitable for light to medium severity operations.
- Contains anti-misting additives.
- Inactive sulphurised ester.
- Has dual purpose as a lubricating oil.

TYPICAL PROPERTIES

Appearance	Amber Oil
Specific Gravity @ 15.6°C	0.861
Kinematic Viscosity @ 40°C	30.0 - 34.0 cSt
Chlorine	No
Sulphur	Yes
Ester	Yes

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.