

# SARCUT STAR CL 22

Last Updated: 09.01.2025  
Product Code: MW0722



SARCUT STAR CL 22 is an extreme pressure neat cutting oil blended from solvent refined mineral oil using selected additives, affording a high level of lubricity and EP performance.

## **APPLICATION**

Suitable for machining a wide range of materials in various applications, including deep hole boring, broaching, heavy duty tapping, threading and gear cutting. Arduous operations are overcome using high performance EP package.

## **BENEFITS**

- Enhanced lubricity.
- Good workpiece visibility.
- Improved finish on machine parts.
- Low oil mist levels.
- Promotes extended tool life.

## **TYPICAL PROPERTIES**

Appearance	Amber Fluid
Specific Gravity @ 15.6°C	0.900 – 0.950
Kinematic Viscosity @ 40°C	19 – 23 cSt
Flashpoint	>200°C
Sulphur	Yes
Chlorine	Yes

Ester: Yes

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.