

SARCUT ULTRA HONING OIL

Last Updated: 09.01.2025
Product Code: MW0007



SARCUT ULTRA HONING OIL is a blend of high quality solvent-refined mineral oil and a carefully balanced EP additive system.

APPLICATION

Use as received as a neat oil for honing operations or any other machining activities where a light viscosity neat oil with excellent lubricity properties is required. Formulated with the additional ability to protect against staining of yellow metals.

BENEFITS

- Excellent cooling properties.
- Enhanced lubricity promotes superior metal wetting and improved surface finish.
- Anti-misting properties for increased operator acceptability.
- Low viscosity ensures exceptional flushing and retention of machined debris and swarf.
- Formulated with inactive sulphur and a copper passivator to ensure protection against yellow metal staining.

PERFORMANCE PROFILE

Heavy duty honing of ferrous and non ferrous materials, can also be used for grinding applications, drilling and general machining. ideal for heavy duty and large diameter applications, such as industrial cylinders and tubes.

TYPICAL PROPERTIES

Colour & Appearance	Amber fluid
Density @ 15.6°C	0.890-0.900 kg/m ³
Kinematic Viscosity @ 40°C	18-20 cSt

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.