

SARDRAW 189

Last Updated: 09.01.2025
Product Code: MW0933



SARDRAW 189 is a high-performance heavy duty drawing lubricant for use of ferrous and non-ferrous materials.

The combination of carefully selected additive technology and base oil structure ensures an extreme pressure performance for deformation of all metals under arduous conditions.

APPLICATION

Designed for use on heavy duty to severe applications such as, heavy duty drawing and stamping, of ferrous and non-ferrous materials.

BENEFITS

- Provides outstanding sulphur free performance.
- Good surface finish.
- Low odour.
- High flash point.
- Extended die life.
- Cost effective.
- Readily removed by solvent degreasing methods.

TYPICAL PROPERTIES

Kinematic Viscosity @ 40°C	35.0 - 40.0 cSt
Appearance	Pale Amber liquid
Flashpoint	> 180°C
Chlorine	Yes
Sulphur	No
Lubricity	Yes
Copper Corrosion	1b

HEALTH & SAFETY, STORAGE AND DISPOSAL

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.