

SARDRAW 46

Last Updated: 09.01.2025
Product Code: MW0570



SARDRAW 46 is a high quality forming and drawing oil blended from solvent refined mineral oil using selected additives, affording a high level of lubricity and EP performance.

(Product formerly known as SARFORM 46)

APPLICATION

Designed for forming, drawing and rolling applications when working with ferrous components. The modern, high performance, ashless EP package also makes this product suitable for many other general machining operations. Application is usually by brush, roller or spray.

Note – not suitable for use with yellow metals as staining may occur.

BENEFITS

- Versatile formulation makes this suitable as a multi-purpose product for machining all types of ferrous metals.
- Enhanced lubricity.
- Low oil mist levels.
- High performance EP package helps promote extended tool life.

TYPICAL PROPERTIES

Appearance	Amber fluid
Specific Gravity @ 15.6°C	0.900
Kinematic Viscosity @ 40°C	41.4-50.6 cSt
Sulphur	Yes
Chlorine	Yes
Ester	Yes

HEALTH & SAFETY, STORAGE AND DISPOSAL

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.