

SARFOOD PAO HYDRAULIC OIL 32

Last Updated: 09.01.2025
Product Code: SFH0032



SARFOOD PAO HYDRAULIC OIL 32 are food grade and non-toxic, developed for hydraulic systems used in food, drink and pharmaceutical processing and packaging equipment. Full synthetic formulation suitable for other hydraulic systems where a clean, non-staining hydraulic oil is desired.

APPLICATION

SARFOOD PAO HYDRAULIC OIL 32 is suitable for hydraulic systems designed to operate in applications where an ISO 32 oil viscosity grades is used. Follow manufacturer's instructions. It is important to purge the system of the previous oil prior to recharging with SARFOOD PAO HYDRAULIC OILS.

BENEFITS

- Low coefficient of friction provides excellent lubrication and reduces wear
- Fully synthetic oil provides extremely wide temperature stability and ensures greatly extended servicing intervals
- Low foaming reduces residue and scum build-up, which extends maintenance intervals.

PERFORMANCE PROFILE

- All ingredients are FDA listed
- Meets the requirements of NSF and InS H1 Guidelines
- Meets the USDA 1998 H1 Guidelines
- All grades contain no genetically-modified ingredients, and do not contain any nut oil or derivatives

TYPICAL PROPERTIES

ISO Grade	32
Appearance	Clear Fluid
Base Fluid	Polyalphaolefin
Temperature Range	- 60°C to +240°C (depending on grade)

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.