

SARFOOD PTFE MULTILUBE 32

Last Updated: 09.01.2025
Product Code: MFL0030



SARFOOD PTFE MULTILUBE 32 is a non-toxic, food grade, multi-purpose lubricant with enhanced penetrating and dewatering properties containing PTFE.

APPLICATION

Specially developed with a non-toxic multi-purpose formulation, ideal for use in slideways, hydraulic systems, and light industrial gearbox applications. Also ideal for use as a light chain oil, and for general lubrication applications where one oil is desired as a multifunctional lubricant, especially in food preparation areas and clean environments.

For best results, Sarfood PTFE Multilube 32 should be shaken thoroughly before use and applied to a previously cleaned surface.

BENEFITS

- Multifunctional performance to help reduce lubricant inventories.
- Very wide operating temperature range of -50°C to +180°C.
- Enhanced anti-wear and dewatering properties.
- Offers excellent penetration and corrosion protection.
- Helps prevent stick / slip on slideways.
- Long life lubricating film with PTFE.
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- FDA listed ingredients under 21 CFR 178.3570

TYPICAL PROPERTIES

Appearance	Pale coloured liquid
Base Oil Type	Synthetic fluid
Viscosity at 40°C cSt	26-32
Solid lubricant	PTFE
Operating Temperature Range	-50°C to +180°C
Copper corrosion test - (IP 112)(ASTM D130)	1b

Recommended storage temperature - should be controlled to between room temperature and max 40°C.

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.