

# SARFORM 313

Last Updated: 09.01.2025  
Product Code: CM0313



SARFORM 313 is a low viscosity mould release agent, formulated with a customised blend of selected mineral based components and high performance ester release additives.

The product is formulated based on advanced low odour mineral oils together with additives to give excellent release characteristics and an enhanced surface finish. Suitable for use on wood, steel, plastic and aluminium mould shuttering.

## **APPLICATION**

Use as received, suitable for use for in brick and concrete forming applications, may be by either brush, roller or spray, (use appropriate respiratory protection if spraying). Avoid excessive build-up of product, especially in tight angles.

## **BENEFITS**

- Provides excellent surface finish.
- Easy separation from the mould.
- Fine spray achieved without clogging spraying equipment.
- Good product mobility at low temperatures.
- Reduces blowholes, surface blemishes and staining.
- Can be used in heated kiln block applications.

## **TYPICAL PROPERTIES**

Appearance	Pale amber liquid
Specific Gravity @ 15°C	0.872
Viscosity @ 40°C	11.00 – 13.00 cSt
Flashpoint °C	> 150

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.