# **SIAIR** Lubricants

SARFORM 327 is a high quality, low viscosity mould release agent designed for modern brick and concrete manufacture. The customised blend of selected hydrocarbon components fortified with chemical release agents gives outstanding results especially with refractory and kiln brick mouldings.

#### **APPLICATION**

Use as received, application may be by either brush, roller or spray, (use appropriate respiratory protection if spraying). Avoid excessive build-up of product, especially in tight angles. Apply on the form face to facilitate the easy removal of components from moulds without damaging the component surface.

#### **BENEFITS**

- Low viscosity, operator friendly formulation.
- Modern low viscosity solvents and surface active release agents combine to produce an environmentally improved formulation.
- Produces good surface finish.
- Excellent separation properties.
- Ease of application.
- Blemish free products.

### **TYPICAL PROPERTIES**

Appearance	Thin, pale liquid
Specific Gravity @ 15°C	0.814
Viscosity @ 40°C	1.92 cSt
Flashpoint °C	70-80

## HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.