

SARFORM 37

Last Updated: 09.01.2025
Product Code: CM0037



SARFORM 37 is a high quality mould release oil formulated using solvent-refined mineral oil, together with hydrocarbon solvent elements and a purpose-designed additive package.

APPLICATION

Developed as a low viscosity product ideal for use in the production of fired clay, tile, brick and concrete products, especially where a very high quality surface finish is desirable.

Application may be by either brush, roller or spray, (use appropriate respiratory protection if spraying). For best results, avoid excessive build-up of product, especially in tight angles.

For ease of application, Sarform 37 is supplied ready for use and requires no additional mixing or stirring before utilisation.

BENEFITS

- Designed to reduce the risk of surface blemishes, blowholes and staining on finished products.
- Operator-friendly formulation with low/reduced odour.
- Suitable for use with all types of plastic or steel moulds and shuttering.
- Low viscosity formulation promotes ease of coverage over the mould surfaces.
- Formulated with the incorporation of effective rust inhibiting properties.

TYPICAL PROPERTIES

Appearance	Pale amber liquid
Specific Gravity @ 15°C	0.839
Viscosity @ 40°C	3.7 cSt
Flash Point °C	81

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.