SIAIR Lubricants

SARFORM BIO is a customised blend of natural vegetable oils and esters which produces a readily biodegradable mould release oil.

APPLICATION

Supplied ready for use, and should be applied as evenly as possible for optimum performance. Application may be by either brush, roller, swab or spray, (use appropriate respiratory protection if spraying). For most economical performance, application by fine spray is recommended. Avoid excessive build-up of product, especially in tight angles.

For new 'unsealed' formwork, pre-treatment is recommended before applying a second coat.

BENEFITS

- Suitable for use on all formworks, concrete and brick.
- No unpleasant odours.
- Designed to show effective rust inhibiting properties.
- Biodegradable formulation does not contain hydrocarbon solvents VOC free.
- Operator-friendly in use for reduced issues with sensitive skin.
- Continued use gives progressively better results on timber formwork.
- Can be used with white or grey cements, as well as concretes containing pigments.
- Drastically reduces the risk of blowholes, staining and surface blemishes.

TYPICAL PROPERTIES

Appearance	Pale amber liquid
Specific Gravity @ 150C	0.905
Viscosity @ 40°C	6.5 cSt
Setting Point	4°C

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.