

SARGREASE CBS 2 is a superior quality, calcium sulphonate complex grease designed to provide exceptional load carrying capability and provide extended lubrication intervals in a wide range of applications.

APPLICATION

Specially developed for the lubrication of all types of plain and anti-friction bearings as well as sliding surfaces which require enhanced levels of water resistance and corrosion protection.

Can be applied by hand, by using a standard grease gun or via a central lubricating system compatible with an NLGI 2 grease.

Please check compatibility before application and use in accordance with equipment manufacturers recommendations.

BENEFITS

- Extends re-lubrication intervals to ensure maximum economy in use and reduced grease consumption
- Highly water resistant formulation offers excellent corrosion protection even when operating in wet conditions or open to the elements
- Excellent EP and anti-wear performance for all types of plain/anti-friction bearings and sliding surfaces

TYPICAL PROPERTIES

Appearance	Smooth, beige grease
Thickener	Calcium Sulphonate Complex
NLGI Classification	No.2
Base Oil Viscosity@40°C (IP71)	220 cSt
Water Washout (IP215, ASTM D1264)	<1%
Dropping Point (ASTM D1264)	>280°C
Operating temperature range	-30°C to +150°C, occasional peak to 220°C

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.