

SARGREASE LC2 is a premium quality mixed soap grease for lubricating all anti-friction and plain bearings subjected to high loads and where water washout or ingress is an issue.

APPLICATION

SARGREASE LC2 grease can be applied manually, or by using a standard grease gun (400gm cartridges available), or via a central lubricating system designed for and capable of pumping an NLGI No.2 grease. As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

BENEFITS

- Exceptional mechanical stability extends re-lubrication intervals.
- Enhanced oxidation stability provides lasting lubrication at high temperatures.
- Excellent anti-wear, load-carrying and shock-load resistance properties to reduce component wear.
- High levels of water resistance and good anti-corrosion capabilities protects components and extends lubricant service life when operating in wet conditions.

TYPICAL PROPERTIES

| | |
|----------------------------------|--------------------------|
| Appearance | Smooth grease |
| Colour | Light Brown |
| NLGI Classification | 2 |
| Thickener | Lithium-Calcium |
| Copper Corrosion (IP112) | Negative |
| Aluminium Corrosion (mod IP112) | Negative |
| Mild Steel Corrosion (mod IP112) | Negative |
| Dropping Point (ASTM D566) | 160°C min |
| Water Washout (IP215) | @ 380C % : 2 @ 790C %: 3 |
| Four Ball Weld Load (IP239) | 285kg |
| Timken OK Load (IP326) | 20kg (45lbs) |
| Operating Temperature Range | -25°C to +140°C |

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.