

SARLUBE OIL 32

Last Updated: 09.01.2025
Product Code: IO0112



SARLUBE OIL 32 is a general purpose machine lubricant manufactured from a blend of solvent refined mineral oils.

APPLICATION

Use as supplied where non-additive lubricants are specified, recommended for lightly loaded industrial equipment with circulating systems, oil baths, automatic lubricators, spray, splash and mist lubricators. Suitable for oil lubricated bearings, machine tool headstocks, and enclosed gearboxes working in light to moderate conditions.

BENEFITS

- Excellent lubricity
- API GL1

TYPICAL PROPERTIES

| | |
|----------------------------|-------------|
| Physical form | Liquid |
| Colour | Pale Amber |
| Odour | Oily |
| Boiling Point (Typical) °C | 220 |
| Viscosity @ 40°C (cSt) | 28.8 - 35.2 |
| Flashpoint °C (C.C) | 197 |
| Density @15.6 °C | 0.867 |

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.