

SARMAX HFC 46

Last Updated: 09.01.2025
Product Code: HG0046



SARMAX HFC 46 is a high quality fire resistant hydraulic fluid blended with polyalkylene glycols in a stable water solution. The formulation includes special chemical additives to inhibit the formation of rust in the system, and provide anti-wear properties. The excellent shear stability and high viscosity index make the product ideal for hydraulic systems subject to long term extremes of temperature and operating conditions.

APPLICATION

Hydraulic equipment used near molten metal, flames or hot surfaces has to be fire resistant, and SARMAX HFC 46 is recommended for use in pressure die casting machines, extruders, presses, furnace flipping devices, forge presses and hammers, glass works, smelting and coking plants.

Water based hydraulic oils are not compatible with mineral oils and the changeover from one to another should be undertaken with care. Further information on material and elastomer compatibility, system design, change over procedure and recommendations when changing to SARMAX HFC 46 can be requested through our Technical Service Department.

BENEFITS

- Superior fire resistance.
- Optimised corrosion and wear protection.
- Low pour point, good shear stability, high viscosity index.
- Compatible with standard packings.

TYPICAL PROPERTIES

Appearance	Pink coloured liquid
ISO Grade	46
Viscosity @ 40°C	43.0 - 49.0
Viscosity Index	> 200
Water Content	44%
IP 135 Rust Test (Part 1)	No rust

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.