SARMAX HYDROL DETERGENT HYDRAULIC OILS - ISO 22

Last Updated: 09.01.2025 Product Code: HY0299

SAR Lubricants

SARMAX HYDROL DETERGENT HYDRAULIC OILS – ISO 22 is a premium quality hydraulic oils, manufactured from a blend of highlyrefined mineral base oils and a multipurpose hydraulic oil additive package with enhanced detergent and dispersing properties.

APPLICATION

For use in both closed and total loss systems where a detergent hydraulic operating fluid is required.

BENEFITS

- Suitable for a wide range of industrial applications.
- Range of viscosities to meet most requirements.
- Reduced viscosity variation with temperature.
- Thermally stable in extreme conditions of temperature and load which supports resistance to degradation.
- Enhanced emulsifying properties to prevent water accumulation.
- Designed to finely disperse impurities and hold in suspension.

PERFORMANCE PROFILE

- DIN 51524 Part 2 (HLP-D)
- ASTM D6158 (HM)
- ISO 6743-4 (HM)

TYPICAL PROPERTIES

ISO Viscosity @ 40°C	22
ISO Viscosity @ 100°C	0.856
Pour Point °C	-26
Flash Point (COC) °C	207

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.