

# SARMAX ULTRA HYDRAULIC OILS - ISO 100

Last Updated: 09.01.2025  
Product Code: HU0100



SARMAX ULTRA HYDRAULIC OILS - ISO 100 is a premium quality industrial hydraulic oil, manufactured from a blend of highly refined and high quality Group II base oils and a multipurpose hydraulic oil additive package.

## **APPLICATION**

For use in both closed and total loss systems where a hydraulic operating fluid is required.

## **BENEFITS**

- Suitable for a wide range of hydraulic and other industrial applications.
- Extensive range of viscosities to meet most requirements.
- Benefiting from a fourfold additive treatment which gives anti-wear, anti-oxidation, anti-corrosion and low foaming properties.
- Thermally stable in extreme conditions of temperature and load which supports resistance to degradation.

## **PERFORMANCE PROFILE**

- DIN 51524 Part 2 (HM, HLP)
- ISO 11158 (HM)
- ASTM D6158 (HM)
- SAE MS1004 (HM)
- Parker-Denison HF-2, HF-1, HF-0 (ISO 32, 46, 68)
- Fives-Cincinnati P-68, P-69, P-70 (ISO 32, 68, 46)
- Eaton E-FDGN-TB002-E
- GB 11118.1-2011 (L-HL, L-HM)
- JCMAS P041 HK Hydraulic specification
- GM LS-2 (ISO 22, 32, 46, 68)
- SEB 181222
- AIST-US Steel 126/127 - R & O Hydraulic Fluids

## **TYPICAL PROPERTIES**

ISO Viscosity @ 40°C, cSt	99.3
ISO Viscosity @ 100°C, cSt	11.9
Viscosity Index	110
Density @ 15°C, Kg/L	0.8667

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.