

SARTEC 40

Last Updated: 09.01.2025
Product Code: IP0392

SARTEC 40 is a medium to long term rust preventative, formulated with a blend of corrosion inhibitors and waxes in a hydrocarbon base which leaves a thin protective film giving excellent indoor storage protection, lasting up to twelve months and some covered outdoor protection.

APPLICATION

Use as received and apply by spray, brush or dipping in a well ventilated area. Leaves a waxy film on drying.

BENEFITS

- Safe on ferrous and non-ferrous metals.
- Provides medium to long term protection of metal components when stored undercover.
- Easily removed with petroleum spirit or other hydrocarbon solvents.
- Good corrosion protection.
- Excellent penetration.
- Non staining.
- Ideal as a protection for agricultural machinery, metal stocks etc.

PERFORMANCE PROFILE

Indoor Protection	12 Months
Outdoor Protection Covered	3-6 Months
Outdoor Protection Uncovered	Not Recommended

TYPICAL PROPERTIES

Appearance	Fluid Oil
Specific Gravity @ 15.6°C	0.841
Colour	Brown
Flash Point	64°C
Kinematic Viscosity @ 40°C	10.0 cSt

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.