

# SARTHERM AO SYN 32

Last Updated: 09.01.2025  
Product Code: IH0868



SARTHERM AO SYN 32 is a premium quality synthetic heat transfer oil for use in closed and low temperature open systems. Based on Group III hydrocracked base fluid the product is formulated to have outstanding thermal stability and oxidation resistance which promotes low carbonisation and resists sludging to meet the most stringent requirements for heat transfer systems.

## **APPLICATION**

Suitable for use in closed and open low temperature heat transfer systems.

## **BENEFITS**

- Excellent thermal oxidation stability.
- Reduction of sludge in operation.
- Protection against corrosion.
- Wide temperature operating range.
- Low evaporation rate.

## **PERFORMANCE PROFILE**

Suitable for systems working in a temperature range of 10°C to 315°C

## **TYPICAL PROPERTIES**

Appearance	Clear, bright colourless liquid
Viscosity @ 40°C	35 cSt
Viscosity @ 100°C	6 cSt
Pour Point	-30°C
Flashpoint (COC)	240°C
Evaporate Loss, NOACK, %	9.0
Nitrogen, ppm	<1
Sulphur, ppm	<1

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.