

SUPER MOLY 5

Last Updated: 09.01.2025
Product Code: GR0781



SUPER MOLY 5 is a premium quality multi-purpose grease for use in all anti-friction bearings subjected to high load conditions. The incorporation of an enhanced molybdenum disulphide content imparts a very high degree of wear protection against load, shock loading and dusty environments. Suitable for use in applications throughout industry and the automotive sector.

APPLICATION

Super Moly 5 can be applied manually or by using a standard grease gun (400gm cartridges available), or via a central lubricating system capable of pumping an NLGI No.2 grease. As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

BENEFITS

- Exceptional extreme pressure and anti-wear additives
- High degree of corrosion protection
- Enhanced adhesive properties to prolong performance profile and product life
- Highly versatile multi-purpose grease

TYPICAL PROPERTIES

Appearance	Smooth Grease
Colour	Grey / Black
NLGI Classification	2
Thickener	Lithium Soap
Base Oil	Mineral Oil
Base Oil Viscosity @ 400C (IP 71) cSt	180
Worked Penetration (IP 50)	265 to 295
Dropping Point (IP 132) 0C	185 min.
Oil Separation (IP 121) %	5 max.
Copper Corrosion (IP 112)	Pass
Resistance To Corrosion Emcor (IP 220)	0 : 0
Water Washout (ASTM D1264) @ 390C %	3
Four Ball Weld Load (IP 239) kgs	450
Timken OK Load (IP 326) lbs	50

Oxidation Stability @ 1000C (IP 142)

Pressure Drop After 100 hrs psi	4
Molybdenum Disulphide Content %	5
Operating Temperature Range	-20°C to +140°C

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)

Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk

Registered in England: 05866783 VAT Registration No: 889171963

SUPER MOLY 5

Last Updated: 09.01.2025
Product Code: GR0781



NOTE: Read and understand all precautions on container labels before using this product.