

SUPERTEC 10 is a light-bodied, solvent based, thin film water-displacing temporary corrosion preventative. Designed to offer inter-operation protection of ferrous and non-ferrous components. It may be used as a water displacing fluid following metalworking operations involving water-based fluids.

Forms a thin light film for short term indoor rust inhibition and protection with excellent dewatering performance, ideal for the storage of components during inter shop processing and protection on tubes, pipes, coiled wire, drawn bar and most components. The product is easily removed by normal cleaning methods.

APPLICATION

To be used as received, application would typically be by dip, brush or spray. Can also be used as a penetrating oil.

BENEFITS

- Good corrosion protection.
- 3 – 6 months indoor protection.
- Excellent water-displacing properties.
- Non-drying protective film.
- Barium free inhibitors.
- Economical – high coverage.
- Penetrating and rust preventative properties.
- Contains fingerprint neutraliser

PERFORMANCE PROFILE

Indoor Protection	3 – 6 Months
Outdoor Protection Covered	Not Recommended
Outdoor Protection Uncovered	Not Recommended

TYPICAL PROPERTIES

Appearance	Fluid Oil
Specific Gravity @ 15.6°C	0.779
Colour	Brown
Flash Point	40°C
Kinematic Viscosity @ 40°C	10.0 cSt

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.