

SYNGEAR MTF 94

Last Updated: 09.01.2025
Product Code: AE0768G

S|AIR Lubricants

SYNGEAR MTF 94 is a premium quality, semi-synthetic gearbox fluid designed for higher output manual transmissions and to meet the requirements of the manufacturers as listed below.

APPLICATION

Primarily designed for manual transmissions which require a fluid to meet MTF 94 specification, particularly Rover vehicles fitted with PG1, PG2 and R65 gearboxes, such as many Rover 25, 45 and MGF models, as well as certain Land Rover, Honda and BMW/MINI vehicles which require this type of product.

BENEFITS

- Excellent frictional characteristics for improved gear change, especially in colder conditions.
- Enhanced resistance to thermal degradation and the effects of oxidation.
- High viscosity index promotes stay-in-grade performance for longer fluid life.
- Excellent cold weather performance.

PERFORMANCE PROFILE

Suitable for use where the following requirements are specified;

- SAE 75w80
- API GL-4
- Rover / Land Rover MTF 94
- Honda MTF94, MTF2
- BMW MTF LT-2

TYPICAL PROPERTIES

Kinematic Viscosity @ 100°C (cSt)	10.3
Kinematic Viscosity @ 40°C (cSt)	64.5
Viscosity Index	147
SG @ 15.6°C	0.874
Flash Point (COC)	>185°C

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.