# SYNMAX 5W-40

Last Updated: 09.01.2025 Product Code: AE0627



SYNMAX 5W-40 is a high-performance, full synthetic engine oil designed for use in both petrol and diesel engines. Designed particularly for modern passenger cars and light commercial vehicles which require a Normal SAPS lubricant of this grade according to latest ACEA requirements.

## **APPLICATION**

Recommended for use as a crankcase lubricant in all vehicles where a Normal SAPS oil of this grade is specified by the manufacturer. Especially suitable for use in many high performance vehicles which require this grade of lubricant.

In addition, the JASO MA2 specification makes it ideally suited for use in many modern high-performance motorcycles.

#### **BENEFITS**

- Latest additive technology offers exceptional wear protection even under extreme operating conditions.
- Provides quick circulation of the oil even under cold start conditions.
- Designed to maximise fuel economy and minimize emissions.
- Formulated to meet many OEM requirements as listed below.

#### **PERFORMANCE PROFILE**

Suitable for use where the following specifications are required;

- API SN/CF
- ACEA A3/B4
- Mercedes Benz 229.1 / 229.3 / 229.5
- Porsche A40
- Renault RN 0700 / RN 0710
- FIAT 9.55535-Z2
- PSA B71 2296
- Vauxhall/Opel/GM LL-A-025/LL-B-025
- JASO MA2 (T903-2011)

#### **TYPICAL PROPERTIES**

0.854
14.9 cSt
168
225°C
-40°C
11.02

### **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.