

SYNMAX MERCURY 0W-20

Last Updated: 09.01.2025
Product Code: AE08027



SYNMAX MERCURY 0W-20 is a full synthetic, fuel efficient petrol/diesel engine oil which combines strong detergency and anti-wear capabilities, together with additional properties to ensure additional protection for modern turbocharged direct injection petrol and diesel engines when service conditions are severe.

APPLICATION

Formulated primarily for use in FORD passenger cars and light commercial diesel engines requiring FORD M2C-952-A1 specification engine oil, it is also recommended for VAUXHALL/OPEL vehicles which require oil to OV 040 1547-A20 standard, as well as for vehicles where GM Dexos D specification is stipulated.

In addition, it is suitable for use in JAGUAR/LAND ROVER petrol engines meeting STJLR.03.5006 specification, and for MERCEDES-BENZ vehicles which specify a 229.71 standard lubricant, as well as other vehicles including hybrid-electric and plug-in hybrid-electric combinations where this grade of oil is specified.

In case of doubt, please refer to vehicle handbook to ensure correct oil specification requirement.

BENEFITS

- Provides additional protection against the potentially adverse effects of using modern bio fuels.
- Designed to cope with extremes of severe service conditions.
- Stay-in-grade properties ensure low levels of volatility at high running temperatures.
- Meets the latest manufacturer requirements to provide LSPI (Low Speed Pre-Ignition) and wear protection for smaller turbocharged direct injection petrol engines.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- ACEA C6/C5
- API SP/SN Plus
- FORD M2C-952-A1
- GM DEXOS D
- JAGUAR/LAND ROVER STJLR.03.5006
- MERCEDES-BENZ 229.71
- VAUXHALL/OPEL OV 040 1547-A20

TYPICAL PROPERTIES

Kinematic Viscosity @ 100°C	8.2
Density @ 15.6°C	0.843
TBN, mg/KOH/g	8.3
Sulphated Ash %	<0.8
Flash Point °C	>200
Pour Point °C	-43

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)

Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk

Registered in England: 05866783 VAT Registration No: 889171963

SYNMAX MERCURY 0W-20

Last Updated: 09.01.2025
Product Code: AE08027



handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.