

UNIVERSAL ANTIFREEZE

50:50

Last Updated: 09.01.2025

Product Code: AF0942

The logo for SAR Lubricants features the letters 'SAR' in a bold, white, sans-serif font inside a red rectangular box. To the right of this box, the word 'Lubricants' is written in a white, sans-serif font against a dark blue background.

UNIVERSAL ANTIFREEZE 50:50 is a high quality ethylene glycol-based pre-mixed engine coolant. The formulation utilizes established inhibitor technology and is free from nitrites, amines and phosphates.

APPLICATION

The pre-mixed 50% formulation is as recommended by most vehicle manufacturers, and is designed to be used as received to provide effective corrosion and frost protection for up to 2 years. Formulated for compatibility with coolant systems in passenger cars, light and heavy commercial vehicles as well as off-highway plant which require this specification of coolant.

BENEFITS

- Suitable for use as a general purpose coolant in most vehicles.
- Provides cold weather and corrosion protection for up to 2 years.
- Free from nitrites, amines and phosphates.

PERFORMANCE PROFILE

Conforms to British Standard BS 6580:2010

TYPICAL PROPERTIES

Appearance	Blue
Conforms to British Standard	BS 6580:2010
Freeze Point Protection	40°C
Specific Gravity	1.06-1.075
pH Value 50% Aqueous Solution	7.8

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.