

Last Updated: 28.08.2014

Product Code: AIR0022

AIRLINE LUBRICANT EP22 is a high-quality low viscosity oil designed for the lubrication of all types of pneumatic tool which require this grade of product.

APPLICATION

Recommended for all types of air tool such as torque wrenches, drills, jackhammers, saws etc. Also suitable for air rams and motors, as well as for general purpose industrial applications.

BENEFITS

- Exceptional EP and anti-wear capabilities to provide protection even in the most demanding conditions
- Formulated for maximum rust and corrosion resistance for extended component life
- Low viscosity ensures rapid circulation to get to work faster
- Excellent anti-foam properties ensures quick release of air from the oil

TYPICAL PROPERTIES

Colour & Appearance:	Pale straw coloured, clear liquid
Density @ 20°C:	0.856 kg/m ³
Kinematic Viscosity @ 40°C:	22 cSt
Kinematic Viscosity @ 100°C:	4.2 cSt

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.