

Last Updated: 28.07.2017
Code: AD0062, AD0063, AD0064

DRIVE TRAIN FLUID TO-4 is a high performance lubricant designed for use in transmissions, final drives and hydraulic systems requiring or meeting Caterpillar TO-4 or Allison C4 requirements. Available in three viscosities to suit different applications and requirements.

BENEFITS

- Excellent friction control prevents clutch slippage and assists with quiet and efficient action of transmissions and brakes.
- Superior wear protection and load carrying.
- Outstanding yellow metal protection.
- Extended drive line component life.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- Caterpillar TO-4 / TO-2
- Allison C4 (off road)
- Euclid
- Termec / TTC*
- Komatsu KES 07.868.1
- Dana*
- Vickers M-2950-S

* Where TO-4 fluid is called for

TYPICAL PROPERTIES

	<u>SAE 10w</u>	<u>SAE 30w</u>	<u>SAE 50w</u>
Appearance:	Dark amber liquid	Dark amber liquid	Dark amber liquid
Density @ 15.6°C:	0.874	0.888	0.899
Kinematic Viscosity @ 100°C (cSt):	4.78	11.87	18.99

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.