

Last Updated: 16.06.2014
Codes: AE0017, AE0009, AE0307

FLEETLUBE 10w, 30w & 40w are monograde engine oils designed to meet the requirements of many naturally aspirated diesel and petrol engines.

APPLICATION

For use in commercial vehicles, vans, plant, off highway plant and passenger cars where this specification of oil is required by the manufacturer.

BENEFITS

An API CG-4/SJ specification diesel/petrol engine oil which can also be used in many transmission and hydraulic applications for plant and off highway equipment which require SAE 10, 30 & 40w viscosities.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API SJ/CG-4
- MIL-L-2104 E
- Detroit Diesel
- MAN 271
- MACK EO-M
- Volvo VDS
- MB 228.1 / 229.1

TYPICAL PROPERTIES

Fleetlube	10w	30w	40w
SAE	10	30	40
Density @ 15°C	0.889	0.884	0.891

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.