

ROCK DRILL OIL 46 is a high-quality, light viscosity oil specially designed for the lubrication of all types of air-operated rock drills, air hammers and other pneumatic equipment which requires this grade of product.

APPLICATION

Primarily recommended for pneumatic percussion-type rock drills, jackhammers and piledrivers, as well as other air-operated equipment such as air saws, riveters and torque wrenches used in mining, quarrying, construction and excavation industries. The lighter grade ensures suitability for all-season operations.

BENEFITS

- Exceptional EP and anti-wear capabilities to provide protection even in the most demanding conditions.
- Formulated for maximum rust and corrosion resistance for extended component life.
- Low viscosity ensures rapid circulation to get to work faster.
- Excellent anti-foam properties ensures quick release of air from the oil.
- The addition of a tackiness additive ensures a constant oil film on cylinder walls and other drill parts even during severe operations.

TYPICAL PROPERTIES

Colour & Appearance:	Dark brown liquid
Density kg/m ³ @ 20°C:	0.886
Kinematic Viscosity cSt @ 40°C:	46
Flash Point °C:	>200
Pour Point °C:	-39

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.