

Last Updated: 26.01.2018

Product Code: IP0916

**SARCOAT PW38 EXTRA** is a high quality, wax film long term rust preventative with a combination of dewatering additive technology together with film-forming corrosion prevention capabilities to provide extensive long-term protection.

Being solvent deposited this wax film corrosion preventive provides long term corrosion protection to all types of components stored outdoors including bar and box sections, aerospace applications such as high-flying aircraft.

## APPLICATION

Use as received, it is recommended that the product is stirred or shaken well before use. In low temperatures, product may gel, but will return to normal consistency under standard working conditions. Apply by spray or brush in a well-ventilated area. Leaves a firm, waxy film on drying, which can be removed when required using hydrocarbon solvents, such as white spirit. If applied by brushing or swabbing extra care must be taken to ensure adequate coverage and that adventitious dirt particulates or brush fibres are not inadvertently introduced which may remain in the film as they can significantly detract from anti-corrosion performance. The ideal application temperature for this product is 15 – 25°C. As below 15°C it will be very viscous.

## BENEFITS

- Contains a highly-efficient dewatering agent to quickly and effectively remove moisture from treated metal surfaces, before leaving a firm, waxy deposit on drying.
- Offers exceptional long-term corrosion protection indoors, and outdoors undercover, for over 5 years, and up to 2 years for open outdoor component storage.
- Compatible with all types of ferrous and non-ferrous metals.
- Excellent penetration qualities to protect normally inaccessible areas.
- Ideal for long term protection of all metal stocks and agricultural machinery, as well as both car and commercial vehicle panels, underbodies etc. especially during storage and restoration.

## TYPICAL PROPERTIES

Appearance:	Opaque fluid
Film thickness:	40-50 microns
Solids Content %:	34-36
Density @ 15.6°C:	0.83
Indoor protection:	5 years +
Outdoor protection:	up to 2 years
Salt Spray ASTM B117	>1000 hours
Coverage	7m <sup>2</sup> per litre at 50 micron
Drying time	@ 20°C to 50 µ film thickness, 3 hours.

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

### **SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)**

Gill Bridge Oil Works, Lowlands Road, MIRFIELD,  
West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371  
Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk

Registered In England: 05866783 VAT Registration No: 889171963



Cert. Number 12669  
ISO 9001