

Last Updated: 16.05.2015  
Product Code: IC 0667

**SARCOOL PREMIUM** is a bio-stable, semi-synthetic soluble cutting fluid concentrate especially suitable for use where the machine tool manufacturers recommend a coolant which contains more than 35% mineral oil.

## BENEFITS

- Compatible with most water qualities.
- Highly resistant to bacterial and fungal degradation.
- Excellent corrosion inhibition to ferrous metals.
- Good resistance to contact corrosion thus allowing work pieces to be stacked without staining occurring.
- Exceptional inhibition properties against staining of many non-ferrous metals, including copper and its alloys and aluminium and its alloys.
- Chlorine, formaldehyde, nitrite and phenol free formulation for optimum operator acceptability.
- Extremely low foaming tendency.

## APPLICATION

(Recommended treat rate 3-8% in water, depending on severity of application. Minimum treat rate 3% in water)

	Turning	Drilling Milling	Sawing	Grinding	Honing	Lapping	Threading	Deep Hole Drilling	Broaching
Steel	✓	✓	✓	✓			✓		
Stainless Steel	✓	✓	✓	✓			✓		
High Alloy Steel	✓	✓	✓	✓			✓		
Titanium									
Carbide									
Cast Iron	✓	✓	✓	✓			✓		
Copper Alloys	✓	✓	✓	✓			✓		
Aluminium Alloys < 7% Si	✓	✓	✓	✓			✓		
Aluminium Alloys > 7% Si									
Plastic	✓	✓	✓	✓			✓		

Water hardness should be checked to determine optimum running concentrations, please consult your SAR Lubricants Sales Engineer for further details.

## TYPICAL PROPERTIES

Appearance	Green liquid, forms a clear, fluorescent emulsion in water
pH (4% emulsion)	9.2 - 9.4
IP 287 Breakpoint	1.5%
IP 125 Corrosion Test	1.0% (no rust)

## FLUID MAINTENANCE

Refractive Index: - 1.32 = % / ° Brix

<i><b>Refractometry data for Sarcool Premium</b></i>	
<i><b>Refractometer reading</b></i>	<i><b>Actual Concentration</b></i>
0	0
1	1.32
2	2.67
3	4.07
4	5.39
5	6.86
6	8.23
7	9.62
8	10.99
9	12.42
10	13.85
11	15.17

## HEALTH & SAFETY, STORAGE AND DISPOSAL

**SARCOOL PREMIUM** should be stored in dry conditions and protected from extreme temperatures: between 4°C and 35°C is the recommended storage temperature.

**SARCOOL PREMIUM** is unlikely to present any significant health or safety hazard when used as recommended by SAR Lubricants. Good standards of personal and industrial hygiene are to be maintained by the user (see Material Safety Data Sheets). In order to protect the environment, the product used should be safely disposed by a licensed contractor. The packaging material should be handled by a recognised reconditioning firm.

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT.

SAR Lubricants assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of SAR Lubricants